

Amphenol LTW Unveils SSL 1.3 "The Bridge" for **Board-to-Board Connection**

Amphenol LTW (ALTW) Smart Solution in Lighting (SSL) supports your LED lighting product development with the board-based technology. SSL 1.3, The Bridge, features the lowest profile jumper connector on the market. It is a space-saving solution to your PCB interconnection as well as the efficient choice for your various board-to-board applications with its solderless design.


Benefits:







2 Low profile 20.0 X 5.1 X 4.5 mm



applications









Flammability Rating

Specifications:

General Specification	
Number of Positions	1P
Connector Size	20.0 X 5.1 X 4.5 mm (H from board)
Screw Size	M2.5 X 0.45
Current Rating	5A (Max)
Voltage Rating	500 VAC/VDC
Dielectric Withstand Voltage	2000 VAC
Durability	10 Cycles
Color	Natural White
Operating Temperature	-40 ~ +105°C
Certifications	UL1977, CSA C22.2 No. 182.3, RoHS
Material Specification	
Housing	Thermoplastic, UL94-V0
Terminal	Copper Alloy, Gold (Selective) over Nickel Plated

For more information, please contact:

Global: Edward Liu (Business Development Manager) | Email: edward_liu@ltw-tech.com

North America: Anson Ting (LED Market Manager) | Email: anson.ting@industrial-amphenol.com

Europe: Darren Boston (Business Development Manager EMEAR, LED Market) | Email: darren_boston@ltw-tech.com

About Amphenol LTW

Amphenol LTW has actively devoted to various outdoor and industrial applications by successfully developing high-end waterproof connectors to meet strict requirements; also has many worldwide patents and certification such as ISO 14001. ISO 9001 and NMEA 2000...etc.. Now Amphenol LTW is not merely a supplier of waterproof connectors but also a solution provider in diversified market segments.

Amphenol LTW Technology Co., Ltd | 9F No. 657-12 Jungjeng Road, Shinjuang District, New Taipei City, Taiwan Telephone: +886-2-2908-5626 | Fax: +886-2-2902-9787 | Website: http://www.amphenolltw.com





Innovation in Waterproof Solution