



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,  
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [ttsales@mail.taisaw.com](mailto:ttsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)

## Product Specifications Approval Sheet

Product Name: SAW Filter 1575.42 MHz SMD 3X3 mm

TST Parts No.:TA0440A

Customer Parts No.: \_\_\_\_\_

Customer signature required
Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: \_\_\_\_\_ Anne Chen *Anne Chen*

Approval by: \_\_\_\_\_ Andy Yu *Andy Yu*

Date: \_\_\_\_\_ 2018/12/10

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,  
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [tstsales@mail.taisaw.com](mailto:tstsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)

## SAW Filter 1575.42 MHz

MODEL NO.: TA0440A

REV. NO.:4

### A. MAXIMUM RATING:

1. Input Power Level: 10 dB<sub>m</sub>
2. DC voltage: 5 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -50°C to +100°C
5. Moisture Sensitivity Level: Level 1 (**MSL 1**)


RoHS Compliant  
Lead free  
Lead-free soldering

### B. ELECTRICAL CHARACTERISTICS:


Item	Min.	Typ.	Max.
<b>Center frequency</b> <b>Fc</b> (dB)	-	1575.42	-
<b>Insertion loss</b> (1574.42~1576.42 MHz) <b>IL</b> (dB)	-	2.9	4.0
<b>Amplitude ripple</b> (1574.42~1576.42 MHz) (dB)	-	0.1	1.5
<b>Attenuation</b> (Reference level from 0 dB)			
1 ~ 890 MHz (dB)	40	60	-
890 ~ 1475 MHz (dB)	36	55	-
1475.42 MHz (dB)	36	50	-
1535.42 MHz (dB)	29	50	-
1615.42 MHz (dB)	25	42	-
1675.42 MHz (dB)	40	55	-
1700 ~ 3000 MHz (dB)	25	38	-
<b>Input/Output VSWR</b> (1574.42~1576.42 MHz)	-	1.55	2.5
<b>Source impedance</b> <b>Zs</b> (Ω)	-	50	-
<b>Load impedance</b> <b>ZL</b> (Ω)	-	50	-

Note1. The standard definitions is in JIS C 6703

### C. MEASUREMENT CIRCUIT:




**D. OUTLINE DRAWING:**





**Date Code Table:**

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

**E. PCB FOOTPRINT:**





# F. FREQUENCY CHARACTERISTICS: Transfer function




# Reflection Functions :

S11




S22




**G. PACKING:**

**1. REEL DIMENSION**

(Please refer to FR-75D10 for packing quantity)



**2. TAPE DIMENSION**



### H. RECOMMENDED REFLOW PROFILE :

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (20~40sec).
4. Time: 2 times.

